

Ice Range

Ice Makers



Features and Benefits

- * Clear Cubed Ice
- * Fully Automatic Operation
- * Stainless Steel Exterior (Galvanised Rear)
- * Adjustable Feet
- * Minimum Water Temperature 5°C
- * Drain Required (pump needed if drain above outlet on ice machine)

Technical Specifications

Operating Range Not suitable for Ambient less than 10°C or more than 32°C

Refrigerant R134A

Type of Defrost Hot gas

Water Consumption

Ice-One 110ltr @ 15°C

Ice-Three 144ltr @ 15°C

Exterior Finish Stainless Steel (Galvanised Rear)

Interior Finish Plastic

Power Required 13 Amp Supply



Ice-One



Ice-Three

Price Reduction On 2013

2 Year Labour Warranty Parts Warranty

1 Year Labour Warranty

We recommend the use of an in-line filter with all Interlevin ice machines, this will help reduce lime scale build up and improve the efficiency and overall lifespan of the unit. Breakdowns associated to lime scale problems are not covered under Warranty.



In Line Filters
 AP3S Kit (Ice One) £125
 HF20S Kit (Ice Three) £175
 Replacement Filters P.O.A.

Dimensions	Height:	Width:	Depth:	Weight:	Kg/24Hr (Max):	Bin Capacity:
Ice-One	738mm	457mm	523mm	39kg	25 (1250 cubes)	14kg
Ice-Three	790mm	457mm	523mm	44kg	38 (1900 cubes)	14kg

*Ice-Three comes with optional legs. Adds 150mm to Height

MODEL	Description	Price	MODEL	Description	Price
Ice-One	Stainless Steel	£935	Ice-Three	Stainless Steel	£1135

CHILLED DISPLAY